

S-CARD

YOUR ACCESS KEY TO SUSTAINABILITY



ADESIVER ELASTIC

SINGLE-COMPONENT ADHESIVE WITH A SILANIC TERMINATION (MS TECHNOLOGY)

Sausage 4200 ml - Sausage 600 ml



Choose Chimiver, together for a sustainable future

PRODUCTS CERTIFICATION



www.emicode.com

GREEN BUILDING PROTOCOLS

| | | | | |
|--|------------------------------------|------------------|--|----------------|
| | V4 | CATEGORY CREDIT | INDOOR ENVIRONMENTAL QUALITY LOW EMITTING MATERIALS | UP TO 3 POINTS |
| | V4.1 | CATEGORY CREDITS | INDOOR ENVIRONMENTAL QUALITY LOW EMITTING MATERIALS | UP TO 3 POINTS |
| | INTERNATIONAL NEW CONSTRUCTION RFO | CREDITS | HEA 02 INDOOR AIR QUALITY | ✓ |
| | V2 | CONCEPT | MATERIALS | ✓ |
| | | FEATURES | X06 VOC RESTRICTIONS | UP TO 4 POINTS |

MINIMAL AMBIENTALS REQUIREMENTS

| | | |
|--|--|---|
| | 2.5.1 EMISSION IN CONFINED SPACES (INDOOR POLLUTION) | ✓ |
|--|--|---|

Documento redatto in collaborazione con

| | | | | | | | | |
|--|--|--|--|-----------------|----------------|---------------|--|--|
| Team LEED® | | | | Team BREEAM® | | | Team WELL® | |
| | | | | | | | | |
| LEED Proven Provider per i protocolli LEED v4ID+C e BD+C | | | | 12 LEED® APBD+C | 2 LEED® APID+C | 2 LEED® APO+M | 3 BREEAM® ASSESSOR/NC 2 BREEAM® ASSESSOR/IFO 2 BREEAM® ASSESSOR/IN USE 2 BREEAM® AP | 7 WELL® AP 1 WELL PTA Performance Testing Agent |

CERTIFICATES OF PERFORMANCE



Choose Chimiver, together for a sustainable future



SHEAR STRENGTH N/mm2

OTHER DATA

| | |
|-------------------|------------|
| RELATIVE DENSITY: | 1,76 KG/Lt |
| VOC | 0,00% |

PACKAGING COMPOSITION

| | | | | |
|------|-----------|-----|------------|---|
| FILM | MATERIALS | ALU | % RECYCLED | - |
|------|-----------|-----|------------|---|



Choose Chimiver, together for a sustainable future