

YOUR ACCESS KEY TO SUSTAINABILITY



ECORAPID

VERY FAST DRYING WATER-BASED SINGLE COMPONENT ACRYLIC-POLYURETHANE PRIMER FOR WOODEN FLOORS



Choose Chimiver, together for a sustainable future

PRODUCTS CERTIFICATION







GREEN BUILDING PROTOCOLS

BUILDING C	V4	CATEGORY CREDIT	INDOOR ENVIRONMENTAL QUALITY LOW EMITTING MATERIALS	UP TO 3 POINTS
LEED WSGBC	V4.1	CATEGORY CREDITS	INDOOR ENVIRONMENTAL QUALITY LOW EMITTING MATERIALS	UP TO 3 POINTS
BREEAM ®	INTERNATIONAL NEW CONSTRUCTION RFO	CREDITS	HEA 02 INDOOR AIR QUALITY	/
WELL BUILDING	V2	CONCEPT	MATERIALS	/
		FEATURES	X06 VOC RESTRICTIONS	UP TO 4 POINTS

MINIMAL AMBIENTALS REQUIREMENTS



2.5.1 EMISSION IN CONFINED SPACES (INDOOR POLLUTION)



2.5.13 b) They do not contain any Cadmium additives, Lead, Hexavalent Chromium, Mercury, Arsenic or Selenium



Documento redatto in collaborazione con



PROVEN PROVIDER

LEED Proven Provider per i protocolli LEED v4ID+Ce BD+C



LEED Fellow LEED Green Associate











3 BREEAM * ASSESSOR NC 2 BREEAM * ASSESSOR INFO 2 BREEAM * ASSESSOR IN USE 2 BREEAM * AP



OTHED DATA

OTHER DATA							
RELATIVE DENSITY:	1,04 KG/Lt						
VOC	9,28%						



PACKAGING COMPOSITION							
TANK	RIALS	HDPE 2	YCLED	-			
САР	MATE	PP 5	% REC	-			

