

# CHIM TABU FD



## Description

CHIM TABU FD is a two-component aliphatic polyurethane primer with special UV ray-absorbing elements. It is non-yellowing and features surface hardness and transparency.

## Characteristics

Mixture ratio	4 CHIM TABU FD 1 INDURITORE N.I. 600 U
Application temperature	+10°C ÷ +25°C
Application	roller 6-8 mm / brush
Thinning (if necessary)	DILUENTE DMC 50
Coverage	100 g/m <sup>2</sup>
Dust dry	30' <sup>(1)</sup>
Fingerprint dry	2 h <sup>(1)</sup>
Pot-Life	3-4 h <sup>(1)</sup>
Sanding	24 h <sup>(1)</sup>
Overcoating without sanding	n.a.
Wood oxidation	marked
Pore filling	good
Storage stability	1 year <sup>(2)</sup>
Packaging	12,5 L (10 + 2,5)
Tool cleaning	DILUENTE DNE
1	at 20°C and 65% R.H.
2	in original sealed containers at temperatures between +10°C and +25°C

## Available Versions

**STD:** transparent to keep the wood natural.  
**COLORATO:** colored in order to change the wood color.

## How to use

Catalyze CHIM TABU FD comp. A with INDURITORE NI 600 U (ratio 4:1). Then dilute with DILUENTE DMC 50 in the proportion of 25% of CHIM TABU FD comp. A. CHIM TABU FD may be applied over a coat of CHIM TABU PRYMER or over a sanded and carefully vacuumed wooden floor. Sanding with 150/180-grit sandpaper must precede a subsequent finishing coat of CHIM TABU FT.

## Label elements

Comp.A

· Highly flammable liquid and vapour. · Pressurized container: may burst if heated. · Causes skin irritation. · May cause drowsiness or dizziness.  
 · Safety data sheet available on request. · Contains 2-hydroxyethyl methacrylate; METHYL METHACRYLATE. May produce an allergic reaction.  
 · Keep away from heat / sparks / open flames / hot surfaces. No smoking. · Keep container tightly closed. · Wash thoroughly with water after use. · Wear protective gloves / protective clothing / eye protection / face protection. · IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. · Call a POISON CENTER or doctor / physician if you feel unwell. · In case of fire: use water to extinguish.  
 Contents:ETHYL ACETATE; N-BUTYL ACETATE ;



Comp.B

· Highly flammable liquid and vapour. · May cause an allergic skin reaction. · May cause drowsiness or dizziness.  
 · Repeated exposure may cause skin dryness or cracking. · Contains isocyanates. May produce an allergic reaction. · Contains HEXAMETHYLENE-DI-ISOCYANATE. May produce an allergic reaction.  
 · If medical advice is needed, have product container or label at hand. · Keep out of reach of children. · Keep away from heat / sparks / open flames / hot surfaces. No smoking. · Keep container tightly closed. · Use only outdoors or in a well-ventilated area. · Wear protective gloves / protective clothing / eye protection / face protection. · Call a POISON CENTER or doctor / physician if you feel unwell. · Dispose your waste in dedicated collection points.  
 Contents:Hexamethylene diisocyanate, oligomers; POLY(TOLYLENE 2,4-DIISOCYANATE); N-BUTYL ACETATE ;



## Web link

Be sure to have the latest version of this technical data sheet downloadable also from the following link:



[http://www.chimiver.com/tds/EN\\_CHIM\\_TABU\\_FD.pdf](http://www.chimiver.com/tds/EN_CHIM_TABU_FD.pdf)