

# Technical Datasheet

Item Code: DDNE000X | Rev.: 2018-10-30 | Ver: 3.0

# **DILUENTE DNE**

## Cleaning tools thinner for polyurethanic solvent based products



### **¤**Description

DILUENTE DNE is a cleaning thinner for tools, rollers, brushes, ect. used for the lacquering with polyurethanic solvent-based lacquers.

#### **¤Characteristics**

Appearance	colourless liquid
Specific weight	0,89 kg/lt
Packaging	5-12,5-25 lt
Storage stability	1 year <sup>(1)</sup>

<sup>1</sup> in original sealed containers at temperatures between +10°C and +25°C

#### **#How to use**

DILUENTE DNE is a thinner recommended for tools cleaning used with poly-urethanic solvent based products. DILUENTE DNE is recommended also for tools cleaning of LIOS BIOIL products.

#### **¤Label elements**

· Highly flammable liquid and vapour. · Suspected of damaging the unborn child. · May be fatal if swallowed and enters airways. · May cause damage to organs through prolonged or repeated exposure. · Causes serious eye damage. · Causes skin irritation.

· Obtain special instructions before use. Keep away from heat / sparks / open flames / hot surfaces. No smoking. Keep container tightly closed. Wear protective gloves / protective clothing / eye protection / face protection. IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. In case of fire: use water to extinguish. Contents:TOLUENE; ISOBUTYL ALCOHOL; ACETONE; N-BUTYL ACETATE;



# ¤Web link

Be sure to have the latest version of this technical data sheet downloadable also from the following link:



http://www.chimiver.com/tds/EN\_DILUENTE\_DNE.pdf

These information are given from the best of our knowledge and technical experience. They are of general character and not binding in any way our company. Every single case should be put to a pratical test by the user who assumes the full responsability of the final result of his work.