

DILUENTE DR 22

Retardant thinner for polyurethanic products



Description

DILUENTE DR 22 is a slow evaporation thinner recommended for polyurethanic single and two-component solvent based lacquers.

Characteristics

Appearance	colourless liquid
Specific weight	0,96 kg/L
Packaging	5-12,5-25 lt
Storage stability	1 year ⁽¹⁾

1 in original sealed containers at temperatures between +10°C and +25°C

How to use


DILUENTE DR 22 has to be added 5-10% to lacquers when weather conditions are difficult as high temperatures or in presence of big surfaces or low absorption woods.

If you add more than the indicated quantity, the final result of the varnished surface couldn't be what expected.

Label elements

· Flammable liquid and vapour.

· Keep out of reach of children. · Keep away from heat / sparks / open flames / hot surfaces. No smoking. · Keep container tightly closed. · Wear protective gloves / protective clothing / eye protection / face protection. · Dispose your waste in dedicated collection points.



Web link

Be sure to have the latest version of this technical data sheet downloadable also from the following link:



http://www.chimiver.com/tds/EN_DILUENTE_DR_22.pdf

These information are given from the best of our knowledge and technical experience. They are of general character and not binding in any way our company. Every single case should be put to a practical test by the user who assumes the full responsibility of the final result of his work.