

Item Code: PPAR001X | Rev.: 23-04-2021 | Ver: 3.5

## Technical Datasheet

# **DILUENTE PULIPAR W**

Water-based liquid cleaner used to remove freshly applied adhesive from pre-finished wooden floor



DILUENTE PULIPAR W is a odorless water-based liquid detergent and it is used for pre-finished wooden floor dirty with single or two-component adhesives after laying. DILUENTE PULIPAR W is effective on adhesives partially hardened for maximum 6 hours (at +20°C, 60% RH). In any case, it is important to intervene before complete adhesive hardening.

#### **¤Characteristics**

Mixture ratio	single-component
Appearance	straw-yellow liquid
Odour	odorless
Application temperature	+10°C ÷ +25°C
Thinning (if necessary)	Ready to use
Application	Cloth
Coverage	20-30 g/m²
Packaging	1 L
Storage stability	1 year <sup>(1)</sup>
	•••••••••••••••••••••••••••••••••••••••

1 in original sealed containers at temperatures between +10°C and +25°C

### ¤How to use

#### In case of fresh adhesive:

Dilute DILUENTE PULIPAR W at 25% in water and pour the solution directly onto the adhesive. Leave to work for a few seconds and rub lightly with a cotton cloth performing rotary movements.

## In the case of particularly resistant or partially hardened adhesives:

Pour the undiluted product directly onto the adhesive and prolong the contact of DILUENTE PULIPAR W with the adhesive avoiding applying to much force; excessive rubbing could alter the gloss of the floor. Possible halos can be removed using a clean rag soaked in VELUREX Cleaner Star. Dab any residue with a dry cloth. It is advisable to always carry out a preliminary test in order to check the chemical resistence of the finish to DILUENTE PULIPAR W.

#### **¤Label elements**



#### **¤Web link**

Be sure to have the latest version of this technical data sheet downloadable also from the following link:



http://www.chimiver.com/tds/EN\_DILUENTE\_PULIPAR\_W.pdf

These information are given from the best of our knowledge and technical experience. They are of general character and not binding in any way our company. Every single case should be put to a pratical test by the user who assumes the full responsability of the final result of his work.