

# PARKETKIT

## Colored acrylic filler parkettkit



### Description

PARKETKIT is a acrylic filler to seal baseboards, joints, between differing flooring elements, etc. May be over-coatable easily after the complete hardening.

### Characteristics

Mixture ratio	single-component
Application temperature	+10°C ÷ +25°C
Application	silicone gun
Colour	oak, walnut, doussiè, iroko, beech-cherry, maple, white, wenge', gray, beige
Joint coverage for leakage 5x5	aprox. 12 linear meters
Joint coverage for leakage 10x10	aprox. 3 linear meters
mm	
Specific weight	white 1,6 kg/L coloured 1,65 kg/L
Maximum open time	15-20' <sup>(1)</sup>
Complete hardening	18-24 h <sup>(1)</sup>
Storage stability	1 year <sup>(2)</sup>
Packaging	310 ml
Tool cleaning	water (with fresh adhesive)

- 1 at 20°C and 65% R.H. for leakage 3/4 mm
- 2 in original sealed containers at temperatures between +10°C and +25°C

### How to use

PARKETKIT may only used on perfectly clean, degreased and dust-free surfaces. After applying, smooth out the joint with a trowel or wet sponge. Repeat the application in case of excess shrinking. After 24 h from the application may be sanded.

### Warnings

For temperatures above 30°C, provide a consumption for a 20% higher. Maximum material allowance is 15 x 15 mm. Low temperatures, high humidity and a considerable leakage can slow down the hardening of the adhesive.

### Label elements



### Web link

Be sure to have the latest version of this technical data sheet downloadable also from the following link:



[http://www.chimiver.com/tds/EN\\_PARKETKIT.pdf](http://www.chimiver.com/tds/EN_PARKETKIT.pdf)