

PARKETTKOLL KX

Vinyl adhesive in water emulsion for wooden floor repairs



Description

PARKETTKOLL KX is a single-component water-based emulsion vinyl adhesive, with a quick setting time characteristic. Uses: PARKETTKOLL KX is used for the repair and the consolidation of wooden floors.

Characteristics

| | |
|-------------------------|--|
| Mixture ratio | single-component |
| Application temperature | +10°C ÷ +25°C |
| Application | smooth trowel |
| Pot-Life | n.a. |
| Maximum open time | 5' ⁽¹⁾ |
| Hardening | 24 h ⁽¹⁾ |
| Coverage | 1000-1300 g/m ² for repairs. 60-100 g/m ² for consolidation. |
| Colour | transparent |
| Storage stability | 1 year ⁽²⁾ |
| Packaging | 5 kg |
| Tool cleaning | Water (before the hardening of the adhesive) |

1 at 20°C and 65% R.H.

2 in original sealed containers at temperatures between +10°C and +25°C

How to use

In case of repairs, remove the pieces of wood which are not perfectly glued to the subfloor, clean the pieces of wood and the subfloor from dust and old glue. Apply a big quantity of PARKETTKOLL KX on the subfloor and re-lay the pieces of wood.

In case of consolidation of old wooden floors, spread the glue (pure or diluted with max. 10% water), with a trowel uniformly on the whole subfloor, especially in between the pieces of wood. Wait for about 24 hours and proceed with sanding and finish of the subfloor.

Label elements

·Safety data sheet available on request.· Contains 1,2-benzisothiazol-3(2H)-one; 2-methyl-4-isothiazolin-3-one. May produce an allergic reaction.

Web link

Be sure to have the latest version of this technical data sheet downloadable also from the following link:



http://www.chimiver.com/tds/EN_PARKETTKOLL_KX.pdf