

PRYMER W

Water-based anti-dusting primer



Description

PRYMER W is a single-component water-based primer recommended to reinforce dust-creating subfloors and to prepare irregular subfloors before levelling with RASOCHIM range of products (see technical data sheets). **Destinations:** anti-dusting.

Characteristics

Mixture ratio	single-component
Application temperature	+10°C ÷ +25°C
Application	8 mm microfiber roller / brush
Thinning	1/5 or 1/6 with water
Coverage	150-200 g/m ²
Pot-Life	n.a.
Storage stability	1 year ⁽¹⁾
Packaging	2,5 kg - 5 kg - 10 kg - 25 kg
Tool cleaning	water on wet primer

1 in original sealed containers at temperatures between +10°C and +25°C

How to use


Reinforcement of dust creating subfloors

Apply PRYMER W diluted in the ratio of 1/5-6 with water onto the subfloor. Wait till it's completely dry (12/24h) and proceed with the laying of the wooden floor. PRYMER W as consolidation of dusting subfloors is recommended when the lay of wooden floors and resilient floors is made with waterbased adhesives (line PARKETTKOLL or line RE 400 see technical data sheet) (

Adhesion promoter for levelling mortars

Apply PRYMER W, diluted in the ratio of 1/5-6 with water on the irregular subfloor, then proceed with smoothing using RASOCHIM range of products (see technical data sheets) while the product is still wet. Before laying down the wooden floor, wait until the subfloor is completely dry.

Label elements



Web link

Be sure to have the latest version of this technical data sheet downloadable also from the following link:



http://www.chimiver.com/tds/EN_PRYMER_W.pdf