

## Technical Datasheet

Item Code: SLOW000X | Rev.: 24-01-2020 | Ver: 3.0

# **SLOWER-**

### Retarding additive for polyurethane adhesives



#### **¤**Description

SLOWER- is an retarding additive for two-component polyurethane adhesives, specifically formulated for ADESIVER GREEN TURF/ADESIVER 327 PU /ADESIVER RE 702. It is used to slow down the setting time of the adhesive and installation of the flooring.

#Characteristics		
Appearance	liquid	
Packaging	200 g	
Storage stability	1 year <sup>(1)</sup>	
Maximum mixing ratio	200 g <sup>(2)</sup>	
1 in original sealed contains	ers at temperatures between +10°C and +25°C	

- 1 in original sealed containers at temperatures between +10°C and +1
- 2 for each 11 kg container of two-component polyurethane adhesive

#### **¤**How to use

Add SLOWER- to component A and mix with an electric drill at low rpm until completely homogeneous. Add component B and proceed as usual.

#### Notes:

Use a maximum of 200 g for each 11 Kg can.

#### POT LIFE of ADESIVER GREEN TURF at different temperatures

	10°C	20°C	35°C
ADESIVER	80 min	65 min	45 min
GREEN TURF			
+ 2% SLOWER-	/	/	65 min

#### **#Web link**

Be sure to have the latest version of this technical data sheet downloadable also from the following link:

 $http://www.chimiver.com/tds/EN\_.pdf$ 

These information are given from the best of our knowledge and technical experience. They are of general character and not binding in any way our company. Every single case should be put to a pratical test by the user who assumes the full responsability of the final result of his work.