

CHIM TABU FT

Non-yellowing, two-component, high-strength aliphatic polyurethane finish



Description

CHIM TABU FT is a two-component aliphatic polyurethane varnish with special UV ray-absorbing elements. It is non-yellowing, scratch-resistant and features surface hardness and transparency. Due to its chemical and physical characteristics, CHIM TABU FT gives the dry varnish's film a pleasing appearance. Uses: finish coat for varnishing coloured and/or dyed wood floors.

Characteristics

Mixture ratio	4 CHIM TABU FT - 1 INDURITORE N.I. 600 U
Application temperature	+10°C ÷ +25°C
Application	roller 6 mm / brush / spray machine
Thinning	DILUENTE DMC 50
Coverage	100 g/m ²
Dust dry	30' ⁽¹⁾
Fingerprint dry	2 h ⁽¹⁾
Pot-Life	3-4 h ⁽¹⁾
Sanding	24 h ⁽¹⁾
Gloss level	60-70 gloss ⁽²⁾
Chemical and physical characteristics	excellent
Coating	good
Storage stability	1 year ⁽³⁾
Packaging	12,5 L (10 + 2,5)
Tool cleaning	DILUENTE DNE

- 1 at 20°C and 65% R.H.
- 2 onto wet film of 90 micron hardened at 20°C and 65% R. H. for 7 days
- 3 in original sealed containers at temperatures between +10°C and +25°C

How to use

When catalysed in the indicated ratios and thinned by 25% with DILUENTE DMC 50, CHIM TABU FT is recommended as a final coat in the subsequent non-yellowing varnish cycle.

- * CHIM TABU PRYMER
- * wait 6 h without sanding
- * CHIM TABU FD
- * wait 12/24 h, then sand with 150/180-grit sandpaper
- * CHIM TABU FT

The maintenance of wooden floors treated with CHIM TABU FT has to be done with VELUREX range of products (see technical data sheets).

Label elements

Comp.A

· Highly flammable liquid and vapour.· Causes skin irritation.· May cause an allergic skin reaction.· May cause drowsiness or dizziness.
· Contains 2-hydroxyethyl methacrylate. May produce an allergic reaction.
· Keep away from heat / sparks / open flames / hot surfaces. No smoking.· Keep container tightly closed.· Wash thoroughly with water after use.· Contaminated work clothing should not be allowed out of the workplace.· Wear protective gloves / protective clothing / eye protection / face protection.· IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.· Call a POISON CENTER or doctor / physician if you feel unwell.

Contents:METHYL METHACRYLATE; N-BUTYL ACETATE ;



Comp.B

· Highly flammable liquid and vapour.· Harmful if inhaled.· Causes skin irritation.· May cause an allergic skin reaction.
· Contains isocyanates. May produce an allergic reaction.· Contains HEXAMETHYLENE-DI-ISOCYANATE. May produce an allergic reaction.
· Keep away from heat / sparks / open flames / hot surfaces. No smoking.· Keep container tightly closed.· Wash thoroughly with water after use.· Contaminated work clothing should not be allowed out of the workplace.· Wear protective gloves / protective clothing / eye protection / face protection.· IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.· Call a POISON CENTER or doctor / physician if you feel unwell.

Contents:Hexamethylene diisocyanate, oligomers; HEXAMETHYLENE-DI-ISOCYANATE; XYLENE (MIXTURE OF ISOMERS); ETHYLBENZENE ;



Web link

Be sure to have the latest version of this technical data sheet downloadable also from the following link:



http://www.chimiver.com/tds/EN_CHIM_TABU_FT.pdf