

CHIM TABU INDUSTRIA

Two component solvent based aliphatic lacquer for wooden floors

Description

CHIM TABU INDUSTRIA is a two-component aliphatic polyurethane lacquer with special UV ray-absorbing elements. It is non-yellowing, scratch-resistant and features surface hardness and transparency. Due to its chemical and physical characteristics, CHIM TABU INDUSTRIA gives the dry lacquer's film a pleasing appearance. Uses: finish coat for varnishing coloured and/or dyed wood floors.

Characteristics

| | |
|---------------------------------------|-------------------------------------|
| Mixture ratio | 4/1 |
| Application temperature | +10°C ÷ +25°C |
| Application | spray / curtain coater |
| Thinning (if necessary) | DILUENTE DMC 50 |
| Coverage | 100 g/m ² |
| Dust dry | 30' ⁽¹⁾ |
| Fingerprint dry | 2 h ⁽¹⁾ |
| Pot-Life | 3-4 h ⁽¹⁾ |
| Sanding | 24 h ⁽¹⁾ |
| Gloss level | 5 / 10 / 25 gloss ⁽²⁾ |
| Chemical and physical characteristics | good |
| Coating | good |
| Storage stability | 1 year ⁽³⁾ |
| Packaging | 12,5 Kg (10 + 2,5) , 25 Kg (20 + 5) |
| Tool cleaning | DILUENTE DNE |

- 1 at 20°C and 65% R.H.
- 2 onto wet film of 90 micron hardened at 20°C and 65% R. H. for 7 days
- 3 in original sealed containers at temperatures between +10°C and +25°C

How to use

When catalysed in the indicated ratios and thinned by 25% with DILUENTE DMC 50, CHIM TABU INDUSTRIA is recommended as a final coat in the subsequent non-yellowing varnish cycle.

- * CHIM TABU PRYMER
- * wait 6 h without sanding
- * CHIM TABU FD
- * wait 12/24 h, then sand with 150/180-grit sandpaper
- * CHIM TABU INDUSTRIA

Use VELUREX Polish WT, VELUREX Metal Lack or VELUREX METAL MATT for normal upkeep and/or extraordinary maintenance of the floor (see technical data sheets).

Label elements

Comp.A

· Highly flammable liquid and vapour. Pressurized container: may burst if heated. Causes skin irritation. May cause drowsiness or dizziness.
 · Safety data sheet available on request. Contains 2-hydroxyethyl methacrylate; METHYL METHACRYLATE. May produce an allergic reaction.
 · Keep away from heat / sparks / open flames / hot surfaces. No smoking. Keep container tightly closed. Wash thoroughly with water after use. Wear protective gloves / protective clothing / eye protection / face protection. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor / physician if you feel unwell. In case of fire: use water to extinguish.
 Contents:ETHYL ACETATE; N-BUTYL ACETATE ;



Comp.B

· Highly flammable liquid and vapour. May cause an allergic skin reaction. May cause drowsiness or dizziness.
 · Repeated exposure may cause skin dryness or cracking. Contains isocyanates. May produce an allergic reaction. Contains HEXAMETHYLENE-DI-ISOCYANATE. May produce an allergic reaction.
 · If medical advice is needed, have product container or label at hand. Keep out of reach of children. Keep away from heat / sparks / open flames / hot surfaces. No smoking. Keep container tightly closed. Use only outdoors or in a well-ventilated area. Wear protective gloves / protective clothing / eye protection / face protection. Call a POISON CENTER or doctor / physician if you feel unwell. Dispose your waste in dedicated collection points.
 Contents:Hexamethylene diisocyanate, oligomers; POLY(TOLYLENE 2,4-DIISOCYANATE); N-BUTYL ACETATE ;

