

ECOWOOD 2K HV INDUSTRY

Two-component water-based polyurethane lacquer with natural anti-reflection effect finish for wooden floors

Description

ECOWOOD 2K HV INDUSTRY is a two-component polyurethane water lacquer for industrial use with a natural effect, suitable for application by coating. The use of special resins gives the floor an extremely opaque, anti-reflective and natural effect. Thanks to its particular formulation ECOWOOD 2K HV INDUSTRY is suitable for painting even dark essences. ECOWOOD 2K HV INDUSTRY is characterized by a high resistance to pedestrian movement and wear.

Characteristics

Mixture ratio	10/1
Application temperature	+10°C ÷ +25°C
Application	Roller coater
Thinning (if necessary)	DILUENTE DR H20
Coverage	70-80 g/m ²
Dust dry	30' ⁽¹⁾
Fingerprint dry	2 h ⁽¹⁾
Pot-Life	2 h ⁽¹⁾
Sanding	16 h ⁽¹⁾
Overcoating without sanding	4 - 12 h ⁽¹⁾
Gloss level	3-5 gloss ⁽²⁾
Chemical and physical characteristics	excellent
Coating	good
Wood oxidation	absent
Storage stability	1 year ⁽³⁾
Packaging	27,5 L (25-2,5)
Tool cleaning	DILUENTE DNH 40 (with fresh product)

1 at 20°C and 65% R.H.

2 onto wet film of 90 micron hardened at 20°C and 65% R. H. for 7 days.

3 in original sealed containers at temperatures between +10°C and +25°C

How to use

ECOWOOD 2K HV INDUSTRY mixed in the indicated ratio is applied by means of roller spreader type machines. Apply 70-80 g/m² of ECOWOOD 2K INDUSTRY on wood previously sanded and after 12-24 hours, after sanding, proceed to the application of the second coat. Ordinary and/or extraordinary maintenance of the floors treated with ECOWOOD 2K HV INDUSTRY must be carried out with the products of the VELUREX line (see related data sheets).

Label elements

Comp.A

· Safety data sheet available on request. Contains Miscela di: 5-cloro-2-metil-2H-isotiazol-3-one; 2-metil-2H-isotiazol-3-one (3:1) 1,2-BENZISOTIAZOLINA 3(2H)-ONE. May produce an allergic reaction.

Comp.B

· May cause respiratory irritation.· May cause an allergic skin reaction.· Harmful to aquatic life with long lasting effects.

· Contains isocyanates. May produce an allergic reaction.

· Wear protective gloves / protective clothing / eye protection / face protection.· Avoid breathing dust / fume / gas / mist / vapours / spray.· Call a POISON CENTER or doctor / physician if you feel unwell.· Store in a well-ventilated place. Keep container tightly closed.

Contents:Hydrophilic aliphatic polyisocyanate ;