

FINITURA ACR-00 GN

Two-component acrylic solvent-based varnish for wooden floors



Description

FINISH ACR-00 GN is a two-component solvent-based acrylic paint. FINISH ACR-00 GN, due to its chemical and physical characteristics, when used as primer / finish, gives the treated floor a pleasant natural effect.

Characteristics

Mixture ratio	10/1
Application temperature	+10°C ÷ +25°C
Application	spray / curtain coater
Thinning (if necessary)	DILUENTE DMC 250
Coverage	100-120 g/m ²
Dust dry	10' ⁽¹⁾
Fingerprint dry	10' ⁽¹⁾
Pot-Life	7 h ⁽¹⁾
Sanding	12 h ⁽¹⁾
Gloss level	3 Gloss ⁽²⁾
Chemical and physical characteristics	good
Coating	good
Storage stability	1 year ⁽³⁾
Packaging	11 L (10 + 1) , 27,5 L (25 + 2,5)
Tool cleaning	DILUENTE DNE
1	at 20°C and 65% R.H.
2	onto wet film of 90 micron hardened at 20°C and 65% R. H. for 7 days
3	in original sealed containers at temperatures between +10°C and +25°C

How to use

FINITURA ACR-00 GN must be catalysed at 10% with INDURITORE ACR-00 and eventually thinned with DILUENTE DMC 250.

NATURAL EFFECT CYCLE:

- * FINITURA ACR-00 GN
- * wait 12-24 h, then sand using 320 grit abrasive paper
- * FINITURA ACR-00 GN

NATURAL EFFECT CYCLE WITH HIGH TRAFFIC RESISTANCE

- * FINITURA ACR-00 GN
- * wait 4-8h
- * FINITURA ACR-00 GN
- * wait 12-24h, then sand using 320 grit abrasive paper
- * FINITURA ACR-771 G05 (see technical data sheets)

MAINTENANCE:

Ordinary and / or extraordinary maintenance of floors treated with FINITURA ACR-00 GN must be done with the products of the VELUREX line (see technical data sheets).

Warnings

FINITURA ACR-00 GN is to be used only on oak and / or light woods. You can use FINITURA ACR-00 GN on reagents. Always carry out preliminary tests.

Label elements

Comp.A	<p>· Highly flammable liquid and vapour. · Causes serious eye irritation. · May cause drowsiness or dizziness.</p> <p>· Repeated exposure may cause skin dryness or cracking.</p> <p>· Keep away from heat / sparks / open flames / hot surfaces. No smoking. · Keep container tightly closed. · Avoid breathing dust / fume / gas / mist / vapours / spray. · Wear protective gloves / protective clothing / eye protection / face protection. · In case of fire: use water to extinguish.</p> <p>Contents:ETHYL ACETATE; N-BUTYL ACETATE ;</p>
Comp.B	<p>· Flammable liquid and vapour. · May cause respiratory irritation. · May cause an allergic skin reaction. · May cause drowsiness or dizziness.</p> <p>· Repeated exposure may cause skin dryness or cracking. · Contains isocyanates. May produce an allergic reaction.</p> <p>· Keep away from heat / sparks / open flames / hot surfaces. No smoking. · Avoid breathing dust / fume / gas / mist / vapours / spray. · Wear protective gloves / protective clothing / eye protection / face protection. · Call a POISON CENTER or doctor / physician if you feel unwell. · In case of fire: use water to extinguish.</p> <p>Contents:HEXAMETHYLENE DIISOCYANATE, OLIGOMER; N-BUTYL ACETATE ;</p>