

FINITURA ACR-771

Two-component acrylic solvent-based varnish for wooden floors



Description

FINITURA ACR-771 is a two-component acrylic-polyurethane varnish with special UV ray-absorbing elements. It is non-yellowing, scratch-resistant and features surface hardness and transparency. Due to its chemical and physical characteristics, FINITURA ACR-771 gives the dry varnish's film a pleasing appearance. Uses: finish coat for varnishing coloured and/or dyed wood floors. CERTIFIED CFS1 ACCORDING TO EN 13501-1.

Characteristics

Mixture ratio	10/1
Application temperature	+10°C ÷ +25°C
Application	spray / curtain machine
Thinning (if necessary)	DILUENTE DMC 50
Coverage	80-120 g/m, CFS1 200 g/m ²
Dust dry	30' ⁽¹⁾
Fingerprint dry	2 h ⁽¹⁾
Pot-Life	3-4 h ⁽¹⁾
Sanding	24 h ⁽¹⁾
Gloss level	5 - 10- 15 Gloss ⁽²⁾
Chemical and physical characteristics	good ⁽²⁾
Coating	good
Storage stability	1 year ⁽³⁾
Packaging	11 KG (10 + 1) , 27,5 KG (25 + 2,5)
Tool cleaning	DILUENTE DNE

- 1 at 20°C and 65% R.H.
- 2 onto wet film of 90 micron hardened at 20°C and 65% R. H. for 7 days
- 3 in original sealed containers at temperatures between +10°C and +25°C

How to use

Catalysed FINITURA ACR-771 with INDURITORE ACR-10 and thinned by 25% with DILUENTE DMC 50 thinner, FINITURA ACR-771 is recommended as a final coat in the subsequent non-yellowing varnish cycle.

- * FONDO ACR-214
- * wait 12 h, then sand with 180/220-grit sandpaper
- * FINITURA ACR-771

The maintenance of wooden floors treated with FINITURA ACR-771 has to be done with VELUREX range of products (see technical data sheets).

Notice: CERTIFIED CFS1 ACCORDING TO EN 13501-1 with a total quantity of 200 g/m²

Label elements

Comp.A

- Highly flammable liquid and vapour. Causes skin irritation. May cause drowsiness or dizziness.
- Contains METHYL METHACRYLATE. May produce an allergic reaction.
- Keep away from heat / sparks / open flames / hot surfaces. No smoking. Keep container tightly closed. Avoid breathing dust / fume / gas / mist / vapours / spray. Wear protective gloves / protective clothing / eye protection / face protection. In case of fire: use water to extinguish.
- Contents:XYLENE (MIXTURE OF ISOMERS); N-BUTYL ACETATE ; ETHYLBENZENE; 2-methoxy-1-methylethyl acetate ;



Comp.B

- Flammable liquid and vapour. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction.
- Repeated exposure may cause skin dryness or cracking. Contains isocyanates. May produce an allergic reaction. Contains HEXAMETHYLENE-DI-ISOCYANATE; TOLUENE-2,4-DI-ISOCYANATE. May produce an allergic reaction.
- Keep away from heat / sparks / open flames / hot surfaces. No smoking. Keep container tightly closed. Wear protective gloves / protective clothing / eye protection / face protection. Wear respiratory protection. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor / physician if you feel unwell. In case of fire: use water to extinguish.
- Contents:TOLUENE-2,4-DI-ISOCYANATE; Hexamethylene diisocyanate, oligomers;N-BUTYL ACETATE ;

