

FINITURA ACR M30

Two-component acrylic solvent laquer for high traffic wooden floors

Description

FINITURA ACR M30 is a two-component acrylic solvent laquer whose main characteristics are the very high abrasion resistance and high traffik resistance.

Characteristics

Mixture ratio	10/1
Application temperature	+10°C ÷ +25°C
Application	spray / curtain machine
Thinning (if necessary)	DILUENTE DMC 50
Coverage	100 g/m ²
Dust dry	30' ⁽¹⁾
Fingerprint dry	2 h ⁽¹⁾
Pot-Life	3-4 h ⁽¹⁾
Sanding	24 h ⁽¹⁾
Gloss level	5 - 10 Gloss ⁽²⁾
Chemical and physical characteristics	good ⁽²⁾
Coating	good
Storage stability	1 year ⁽³⁾
Packaging	27,5 KG (25 + 2,5)
Tool cleaning	DILUENTE DNE

1 at 20°C and 65% R.H.
 2 onto wet film of 90 micron hardened at 20°C and 65% R. H. for 7 days
 3 in original sealed containers at temperatures between +10°C and +25°C

How to use

FINITURA ACR M30 mixed with INDURITORE ACR M30 and thinned by 25% with DILUENTE DMC 50, is used in the following high traffic varnishing cycle:

- * FINITURA ACR M30
- * wait 12h, then sand with abrasive sandpaper 180/220 grit
- * FINITURA ACR M30

The maintenance of wooden floors treated with FINITURA ACR M30 has to be done with VELUREX range of products (see technical data sheets).

Label elements

Comp.A

· Highly flammable liquid and vapour.· May be fatal if swallowed and enters airways.· May cause damage to organs through prolonged or repeated exposure.· Causes serious eye irritation.· Causes skin irritation.· May cause drowsiness or dizziness.

· Contains METHYL METHACRYLATE. May produce an allergic reaction.

· Keep away from heat / sparks / open flames / hot surfaces. No smoking.· DO NOT induce vomiting.· Wear protective gloves / protective clothing / eye protection / face protection.· IF SWALLOWED: Immediately call a POISON CENTER or doctor / physician.· In case of fire: use water to extinguish.

Contents:XYLENE (MIXTURE OF ISOMERS) N-BUTYL ACETATE ETHYLBENZENE;



Comp.B

· Flammable liquid and vapour.· Harmful if inhaled.· May cause respiratory irritation.· May cause allergy or asthma symptoms or breathing difficulties if inhaled.· May cause an allergic skin reaction.· May cause drowsiness or dizziness.

· Repeated exposure may cause skin dryness or cracking.· Contains isocyanates. May produce an allergic reaction.

· Keep away from heat / sparks / open flames / hot surfaces. No smoking.· Avoid breathing dust / fume / gas / mist / vapours / spray.· Wear protective gloves / protective clothing / eye protection / face protection.· Wear protective gloves / protective clothing / eye protection / face protection.· IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

Contents:Hexamethylene diisocyanate, oligomers M-TOLYLIDENE DIISOCYANATE Polyisocyanates BASED HEXAMETHYL DIISOCYANATE / TOLUENE DIISOCYANATE N-BUTYL ACETATE;

