

FINITURA DC SV 0024

Two-component acrylic solvent laquer, with dual-cure technology, for wooden floors.



Description

FINITURA DC SV 0024 is a two-component acrylic solvent laquer, with double cross-linking (UV + Induritore DC 0018). Suitable for industrial applications, spray or via curtain coater, it allows to obtain a natural effect.

Characteristics

Mixture ratio	10/0,5
Application temperature	+10°C ÷ +25°C
Application	spray / curtain machine
Thinning (if necessary)	DILUENTE per VERNICI UV
Coverage	60-100 g/m ²
Pot-Life	3-4 h ⁽¹⁾
Sanding	immediata dopo lampade UV ⁽¹⁾
Gloss level	5 - 10 Gloss ⁽²⁾
Chemical and physical characteristics	good ⁽²⁾
Storage stability	1 year ⁽³⁾
Packaging	22,5 L (20 + 2,5)
Tool cleaning	DILUENTE DNE

- 1 at 20°C and 65% R.H.
- 2 onto wet film of 90 micron hardened at 20°C and 65% R. H. for 7 days
- 3 in original sealed containers at temperatures between +10°C and +25°C

How to use

FINITURA DC SV 0024, mixed with INDURITORE DC 0018 and diluted in the measure of 30% with DILUENTE PER VERNICI UV, is recommended as a final coat in the following painting cycle:

- * FONDO DC SV 0011 (see relative technical data sheet)
- * IR oven
- * UV lamps
- * Sand using 220/320 grit sandpaper
- * FINITURA DC SV 0024
- * IR oven
- * UV lamps

As an alternative to FONDO DC SV 0011, you can give two coats of FINITURA DC SV 0024.

The ordinary and/or extraordinary maintenance of the floors treated with FINITURA DC SV 0024 must be done with the products of the VELUREX line (see related technical data sheets).

Label elements

· Highly flammable liquid and vapour. · Causes serious eye damage. · Causes skin irritation. · May cause an allergic skin reaction. · May cause drowsiness or dizziness.

· Contains OSSIDO DI DIFENIL (2,4,6 - TRIMETILBENZOIL) FOSFINA. May produce an allergic reaction.

· Keep away from heat / sparks / open flames / hot surfaces. No smoking. · IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. · Wear protective gloves / protective clothing / eye protection / face protection. · Immediately call a POISON CENTER or doctor / physician. · In case of fire: use water to extinguish.

Contents: DIACRILATO DI OSSIBIS (METIL- 2,1- ETANDIILE); N-BUTILE ACETATO; ACETATO DI ETILE;

