

FINITURA UV R79

UV Lacquer based on special acrylic resins



Description

Single-component photoactivated product based on special acrylic resins, used as a finishing coat for matte effect for varnishing of wooden floors, furniture, doors and panels. It's characterized by excellent hardness, thermal expansion and uniformity of gloss.

Characteristics

| | |
|---------------------------------------|---|
| Preparation | photoactivated |
| Thinning (if necessary) | DILUENTE MONOMERICO |
| Application temperature | +10°C ÷ +25°C |
| Viscosity | 40" - 50" Ford Cup 6 |
| Application | single head roller coater / twin head roller coater / engraved roller |
| Coverage | 7/15 g/m ² |
| Flash-Off | n.a. |
| Hardening | 2/3 mercury lamps 80W cm ² |
| Gloss level | 5 gloss |
| Dry residue | 99% |
| Chemical and physical characteristics | excellent |
| Storage stability | 1 year ⁽¹⁾ |
| Packaging | 25 KG |
| Machine cleaning | DILUENTE ACETONE |

1 in original sealed containers at temperatures between +10°C and +25°C

How to use

Shake well before use.

FINITURA UV R79 is a UV finisher suitable for application by roller machine such as baby and roller laser. FINITURA UV R79 is generally applied on wooden floors previously treated with apposite primers. The regular and intense maintenance of wooden floors treated with FINITURA UV R79 should be made with the VELUREX products line (see technical data sheet).

Label elements

· For more information about the safe use of the product it is recommended to consult the latest version of the Safety Data Sheet.