

# INDURITORE ACR 10

## Hardener for acrylic products

### Description

INDURITORE ACR 10 is a hardener for acrylic products of the ACR line.

### Characteristics

Mixture ratio	10%
Storage stability	1 year <sup>(1)</sup>
Packaging	2,5 L

1 in original sealed containers at temperatures between +10°C and +25°C

### Label elements

· Flammable liquid and vapour. · May cause respiratory irritation. · May cause allergy or asthma symptoms or breathing difficulties if inhaled. · May cause an allergic skin reaction. · May cause drowsiness or dizziness.

· Contains isocyanates. May produce an allergic reaction. · Repeated exposure may cause skin dryness or cracking.

· Keep away from heat / sparks / open flames / hot surfaces. No smoking. · Avoid breathing dust / fume / gas / mist / vapours / spray. · Wear protective gloves / protective clothing / eye protection / face protection. · If experiencing respiratory symptoms: call a POISON CENTER or doctor / physician. · IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

Contents: M-TOLYLIDENE DIISOCYANATE Hexamethylene diisocyanate, oligomers Polyisocyanates BASED HEXAMETHYL DIISOCYANATE / TOLUENE DIISOCYANATE N-BUTYL ACETATE;



These information are given from the best of our knowledge and technical experience. They are of general character and not binding in any way our company. Every single case should be put to a practical test by the user who assumes the full responsibility of the final result of his work.