

INDURITORE N.I. 600 U

Hardener for acrylic products

Description

INDURITORE N.I. 600 U is a hardener for the CHIM TABU line of acrylic products.

Characteristics

Mixture ratio	10%
Storage stability	1 year ⁽¹⁾
Packaging	2,5 L

1 in original sealed containers at temperatures between +10°C and +25°C

Label elements

· Flammable liquid and vapour. Harmful if inhaled. May be fatal if swallowed and enters airways. May cause damage to organs through prolonged or repeated exposure. Causes serious eye irritation. Causes skin irritation. May cause respiratory irritation. May cause an allergic skin reaction. May cause drowsiness or dizziness.

· Contains isocyanates. May produce an allergic reaction.

· Keep away from heat / sparks / open flames / hot surfaces. No smoking. DO NOT induce vomiting. Wear protective gloves / protective clothing / eye protection / face protection. IF SWALLOWED: Immediately call a POISON CENTER or doctor / physician. In case of fire: use water to extinguish.

Contents:XYLENE (MIXTURE OF ISOMERS) Hexamethylene diisocyanate, oligomers 2-METHOXY-1-METHYLETHYL ACETATE N-BUTYL ACETATE ;



These information are given from the best of our knowledge and technical experience. They are of general character and not binding in any way our company. Every single case should be put to a practical test by the user who assumes the full responsibility of the final result of his work.