

# ISOLANTE WR 5190 UV

## Two-component sealing primer



### Description

ISOLANTE WR 5190 UV is a two-component sealing primer used to improve the adhesion of subsequent finishing coats on hard-to-treat substrates (such as prefinished UV).

### Characteristics

Mixture ratio	5/1
Application temperature	+10°C ÷ +25°C
Application	Mohair roller 6 mm
Thinning (if necessary)	DILUENTE DMC 50
Coverage	60 - 90 g/m <sup>2</sup>
Dust dry	20' <sup>(1)</sup>
Fingerprint dry	1 h <sup>(1)</sup>
Sanding	do not sand
Overcoating without sanding	min 60' - max 120'
Storage stability	1 year <sup>(2)</sup>
Packaging	12 L (10+2) - 30 L (25+5)
Tool cleaning	DILUENTE DNE

1 at 20°C and 65% R.H.

2 in original sealed containers at temperatures between +10°C and +25°C

### How to use

After having carefully sanded the support with 180 grit sandpaper, proceed with the application of ISOLANTE WR 5190 UV according to the methods shown.

After 60' but no more than two hours, apply, without sanding, the finishing coat, such as: DUROLACK MC 50, ECOSTAR 2K, ECOWOOD 2K, ECOSTAR 2K COLORATA or ECOTRAFFIK 2K.

In case of tracing the lines or filling the areas of a playing field, after the application of the first coat of ECOSTAR 2K COLORATA, you can apply a second coat in the methods shown in the relevant data sheet.

### Label elements

Comp.A

· Highly flammable liquid and vapour. Causes serious eye irritation. May cause drowsiness or dizziness.  
 · Repeated exposure may cause skin dryness or cracking.  
 · Keep away from heat / sparks / open flames / hot surfaces. No smoking. Keep container tightly closed. Wash thoroughly with water after use. Wear protective gloves / protective clothing / eye protection / face protection. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor / physician if you feel unwell.

Contents:ETHYL ACETATE; N-BUTYL ACETATE ;



Comp.B

· Highly flammable liquid and vapour. Causes serious eye irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause drowsiness or dizziness.

· Repeated exposure may cause skin dryness or cracking.

· If medical advice is needed, have product container or label at hand. Keep out of reach of children. Keep away from heat / sparks / open flames / hot surfaces. No smoking. Keep container tightly closed. Wear protective gloves / protective clothing / eye protection / face protection. Wear respiratory protection. Call a POISON CENTER or doctor / physician if you feel unwell. Dispose your waste in dedicated collection points.

Contents:ETHYL ACETATE; Tris(4-isocyanatophenyl) thiophosphate ;



### Web link

Be sure to have the latest version of this technical data sheet downloadable also from the following link:

[http://www.chimiver.com/tds/EN\\_.pdf](http://www.chimiver.com/tds/EN_.pdf)