

LIOS BALM Fissativo

Protective oil for oiled wooden floors



Description

Suitable product that gives to the wooden floor treated with LIOS BALM Fissativo better durability and water-repellance characteristics.

Characteristics

Application	cloth
Application temperature	+10°C ÷ +25°C
Thinning (if necessary)	DILUENTE LIOS SOLV
Surface dry time	12-24 h ⁽¹⁾
Total drying time	15 days ⁽¹⁾
Sanding	not for sanding
Painting over	6-8 h
Coverage	30 m ² /L (depending on the porosity of the wood)
Storage stability	1 year ⁽²⁾
Packaging	2 L - 5 L - 10 L - 25 L
Tool cleaning	DILUENTE DNE

1 at 20°C and 65% R.H.

2 in original sealed containers at temperatures between +10°C and +25°C

How to use

Shake well before use.

Apply LIOS BALM Fissativo uniformly using a cloth.

In case of particularly absorbent woods, in order to increase the walking resistance, apply a second coat of LIOS BALM Fissativo. Such operation would be made without sanding as soon the first coat is walkable (6-8 hours).

Warnings

Cloths, sponges, pads used for the application (even sanding dust), must be soaked immediately after use in order to avoid the risk of self-ignition.

Label elements

- Flammable liquid and vapour.
- Repeated exposure may cause skin dryness or cracking. Contains 2-BUTANONE OXIME. May produce an allergic reaction.
- Keep away from heat / sparks / open flames / hot surfaces. No smoking. Keep container tightly closed. Wear protective gloves / protective clothing / eye protection / face protection. IF ON SKIN (or hair): Remove / Take off immediately all contaminated clothing. Rinse skin with water / shower. In case of fire: use water to extinguish.



Web link

Be sure to have the latest version of this technical data sheet downloadable also from the following link:



http://www.chimiver.com/tds/EN_LIOS_BALM_Fissativo.pdf