

# PRYMER UV R120

UV Primer based on special unsaturated acrylic resins



## Description

Single/two component photoactivated product based on special unsaturated acrylic resins used as a primer for the varnishing of wooden floors, furniture, doors and panels. It's particularly suitable for varnishing of supports with deep pore, such as teak and wenge, where often there is the classic problem of "silvering" of the pore. It's characterized by excellent mechanical performance, tenacity and transparency. The adhesion to difficult surfaces improves considerably, when it's used with INDURITORE UV 100.

## Characteristics

Preparation	photoactivated
Possible mixture	10% INDURITORE UV 100
Thinning (if necessary)	DILUENTE MONOMERICO
Application temperature	+10°C ÷ +25°C
Application	roller machine
Coverage	15/20 g/m <sup>2</sup>
Flash-Off	n.a.
Hardening	1 mercury lamps 360
Sanding	n.a.
Overcoating without sanding	n.a.
Wood oxidation	excellent
Colour	amber
Viscosity	80" - 90" Ford Cup 6
Specific weight	1,1 Kg/L
Dry residue	99%
Storage stability	6 months <sup>(1)</sup>
Packaging	25 KG
Machine cleaning	DILUENTE ACETONE

1 in original sealed containers at temperatures between +10°C and +25°C

## How to use

PRYMER UV R120 is a adhesion primer suitable for application by single head roller coater as a coater and curable by high-pressure UV lamps. PRYMER UV R120 is used as a adhesion coat on woods particularly difficult to treat and, after semi-drying, by 1 high-pressure lamp, overcoating with UV filling/sanding primer.

## Label elements

· Causes serious eye irritation. · Causes skin irritation. · May cause respiratory irritation. · May cause an allergic skin reaction. · Toxic to aquatic life with long lasting effects.

· Contains PHENYL BIS(2,4,6-TRIMETHYLBENZOYL)-PHOSPHINE OXIDE. May produce an allergic reaction.

· Wash thoroughly with water after use. · Contaminated work clothing should not be allowed out of the workplace. · Avoid release to the environment. · Wear protective gloves/protective clothing/eye protection/face protection. · IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. · Call a POISON CENTER or doctor/physician if you feel unwell. · Store in a well-ventilated place. Keep container tightly closed.

Contents: OXYBIS(METHYL-2,1-ETHANEDIYL) DIACRYLATE; TRI (PROPYLENE GLYCOL) DIACRYLATE, MIXTURE OF ISOMERS; HYDROXYPROPYL METHACRYLATE; BISPHENOL A EPOXY DIACRYLATE; NEOPENTYL GLYCOL PROPOXYLATE DIACRYLATE;

