

# UV OIL ONE 1317 Colorato

## UV lacquer oil-based

### Description

UV coloured lacquer based on oil modified acrylate oligomers, suitable for lacquered wooden floors. Wooden floors treated with UV OIL ONE 1317 are characterized by excellent hardness, flowing and elasticity. It gives the wood a warm and natural look.

### Characteristics

Mixture ratio	ready to use
Colour	different colours available
Thinning (if necessary)	DILUENTE MONOMERICO
Application temperature	+10°C ÷ +25°C
Application	roller machine
Coverage	10/15 g/m <sup>2</sup>
Flash-Off	n.a.
Hardening	1-3 mercury lamps 360
Pot-Life	n.a.
Sanding	immediate after hardening
Overcoating without sanding	n.a.
Wood oxidation	n.a.
Gloss level	5 or 10 gloss
Dry residue	99%
Viscosity	140" - 150" Ford Cup 4
Specific weight	1,05 Kg/L
Chemical and physical characteristics	excellent
Storage stability	1 year <sup>(1)</sup>
Packaging	25 KG
Machine cleaning	DILUENTE ACETONE

1 in original sealed containers at temperatures between +10°C and +25°C

### How to use

UV OIL ONE 1317 coloured version is meant to be used as first coat on stained cycle. It can be applied by single head roller coater such as coater and baby. It has to be applied on sanded and properly prepared wood. It cures by high-pressure UV lamps. To achieve the best results we advice to apply, depending on wood species and customer needs, 1 or 2 coats of the coloured version, and 1 or 2 coats of the clear one. Regular and intense maintenance has to be done with Velurex Cleaner Star.

### Label elements

· Causes serious eye irritation. · Causes skin irritation. · May cause respiratory irritation. · May cause an allergic skin reaction. · Harmful to aquatic life with long lasting effects.

· Contains 2-HYDROXYETHYL METHACRYLATE. May produce an allergic reaction.

· Avoid breathing dust / fume / gas / mist / vapours / spray. · Wash thoroughly with water after use. · Wear protective gloves / protective clothing / eye protection / face protection. · Call a POISON CENTER or doctor / physician if you feel unwell. · Store in a well-ventilated place. Keep container tightly closed.

Contents: 1,6-HEXANEDIOL DIACRYLATE; 1-METHYL-1,2-ETHANEDIYL]BIS[OXY(1-METHYL-2,1-ETHANEDIYL)] DIACRYLATE; ACRYLATE; MESITYLENE;

