

## Technical Datasheet

Item Code: CUSL000X | Rev.: 31-01-2024 | Ver: 3.7

# ANTISLIP PROFESSIONAL

**Concentrated, highly effective water-based no-slip solution**



\* Pack 1L

### Description

ANTISLIP PROFESSIONAL is a concentrated, water-based, no-slip solution that does not require rinsing, it's not aggressive and does not alter the surface. It is ideal for preventing and limiting the risk of falling. It can be used on most hard surfaces (lacquered wooden floors, ceramic, stoneware, marble, resin, microcement, PVC, LVT, SPC, etc). Furthermore, thanks to its formulation it does not stain and doesn't film.

### Characteristics

Application	cloth / mop / sponge
Thinning (if necessary)	water
Storage stability	1 year <sup>(1)</sup>
Packaging	1 L - 5 L
Tool cleaning	water

1 in original sealed containers at temperatures between +10°C and +25°C

### How to use

Shake the product well before use.

Clean the surface to be treated thoroughly with the specific cleaner (see VELUREX line) and let it dry, dilute ANTISLIP PROFESSIONAL and then proceed with the application.

1 L packaging: dilute 3 caps (150 ml) with 1 L of water.

5 L packaging: dilute 750 ml of product with 5 L of water (concentration 15%).

Recommended frequency: repeat the treatment as needed and at regular intervals.

90% Biodegradability

#### Coverage

3 caps + 1 L of water	1 L of diluted product in the ratios indicated
70 m <sup>2</sup> /L	500 m <sup>2</sup> /L

### Warnings

Keep away from children. If consulting a doctor, keep the product container or label.

### Label elements

For more information about the safe use of the product it is recommended to consult the latest version of the Safety Data Sheet.

### Web link

Be sure to have the latest version of this technical data sheet downloadable also from the following link:



[http://www.chimiver.com/tds/EN\\_ANTISLIP\\_PROFESSIONAL.pdf](http://www.chimiver.com/tds/EN_ANTISLIP_PROFESSIONAL.pdf)

These information are given from the best of our knowledge and technical experience. They are of general character and not binding in any way our company. Every single case should be put to a practical test by the user who assumes the full responsibility of the final result of his work.