

ATTAKKO PRO MAX

Fast-setting silane adhesive for skirting boards and vertical elements



Description

ATTAKKO PRO MAX is a one-component silane adhesive sealant that cures by reacting with moisture in the air. It is an adhesive for assembly applications requiring strong initial grab, ideal for vertical bonding of skirting boards and profiles on all substrates commonly used in construction (glass, porcelain, wood, aluminium, steel, iron, concrete, plasterboard, polystyrene). It features a high solid content, excellent thixotropy and very low emission of volatile organic compounds

Characteristics

Mixture ratio	single-component
Application temperature	+10°C ÷ +25°C
Application	silicone gun
Coverage	10 linear meter / 290 ml cartridge
Specific weight	1,42 Kg/L
Maximum open time	30' ⁽¹⁾
Hardening	24 h ⁽¹⁾
Break resistance (DIN53504)	2,10 N/mm ²
Tensile strength at break (DIN53504)	400 %
Elastic modulus at 100% (DIN53504)	1,10 N/mm ²
Shore A hardness test(DIN53505)	45
Colour	white
Storage stability	2 years ⁽²⁾
Packaging	290 ml
Tool cleaning	DILUENTE ACETONE

- 1 at 20°C and 65% R.H.
- 2 in original sealed containers at temperatures between +10°C and +25°C

How to use

The surfaces to be bonded must be clean, non-friable and perfectly degreased. Apply ATTAKKO PRO MAX in a continuous wavy bead on the material to be bonded. Do not wait more than 20 minutes before positioning the product, applying strong and even pressure. The adhesive will grab immediately and maximum strength will be reached within 24/48 hours. Remove excess fresh adhesive with a damp cloth. Application at temperatures below +5°C is not recommended.

Label elements

For more information about the safe use of the product it is recommended to consult the latest version of the Safety Data Sheet.

Web link

Be sure to have the latest version of this technical data sheet downloadable also from the following link:

http://www.chimiver.com/tds/EN_ATTAKKO_PRO_MAX.pdf