

# FINITURA DC SV-LED 932

**Two-component acrylic solvent LED lacquer, with dual cure technology, for wooden floors.**



## Description

FINITURA DC SV-LED 932 is a two-component, double cross-linking acrylic solventborne lacquer (LED + Induritore DC 0018). Suitable for industrial spray applications, it allows to obtain a natural finish effect.

## Characteristics

Mixture ratio	5% INDURITORE DC 0018
Application temperature	+10°C ÷ +25°C
Application	Spray / Curtain Coater
Thinning (if necessary)	DILUENTE per VERNICI UV
Coverage	60-100 g/m <sup>2</sup>
Pot-Life	3-4 h
Sanding	immediate after curing with UV lamps
Gloss level	5 - 10 Gloss
Chemical and physical characteristics	good
Storage stability	1 year <sup>(1)</sup>
Packaging	22,5 L (20 + 2,5)
Machine cleaning	DILUENTE DNE

1 in original sealed containers at temperatures between +10°C and +25°C

## How to use

Shake well before use.

FINITURA DC SV-LED 932, mixed with INDURITORE DC 0018 and diluted in the measure of 30% with DILUENTE PER VERNICI UV, is used in the following cycle:

- \* FINITURA DC SV-LED 932
- \* Flash off ca. 10' 35/40°C
- \* LED lamps
- \* Sand with abrasive sandpaper grit 220/320
- \* FINITURA DC SV-LED 932
- \* Flash off ca. 10' 35/40°C
- \* LED lamps

The ordinary and/or extraordinary maintenance of floors treated with FINITURA DC SV-LED 932 must be done with the products of the VELUREX line (see relative data sheets).

## Label elements



· For more information about the safe use of the product it is recommended to consult the latest version of the Safety Data Sheet.