

FONDO ACR-214

Fast drying, non-yellowing two component acrylic primer



Description

FONDO ACR-214 is an acrylic two component fast drying primer. It is leaving the wood extremely natural giving a flat and untreated look.

Characteristics

Mixture ratio	10% INDURITORE ACR-10
Application temperature	+10°C ÷ +25°C
Application	spray / curtain
Thinning (if necessary)	DILUENTE DMC 50
Coverage	100-120 g/m ²
Dust dry	30' ⁽¹⁾
Fingerprint dry	2 h ⁽¹⁾
Pot-Life	3-4 h ⁽¹⁾
Sanding	24 h ⁽¹⁾
Overcoating without sanding	n.a.
Wood oxidation	n.a.
Pore filling	good
Storage stability	1 year ⁽²⁾
Packaging	25 L (20+5) - 12,5 l (10+2,5)
Tool cleaning	DILUENTE DNE

1 at 20°C and 65% R.H.

2 in original sealed containers at temperatures between +10°C and +25°C

How to use

Shake well before use.

FONDO ACR-214 has to be mixed with 10% of INDURITORE ACR 10 and diluted with 25% of DMC50. It can be applied directly on raw wood or on wood already colored. Before applying the top coat sand with 280/320 paper grit.

Note:

Run an adhesion test when the application of FONDO ACR 214 has to be done on wood already colored.

Label elements

· For more information about the safe use of the product it is recommended to consult the latest version of the Safety Data Sheet.