

FONDO UV R37-G10

UV Primer based on special acrylic resins

Description

Single-component photoactivated product based on special acrylic resins used as a filler primer to paint parquets, furniture, doors, panels, etc. Particularly suitable in brushed cycles to avoid the phenomenon of "glossy pore". It has excellent stretch, good sanding, excellent clinging and transparency.

Characteristics

Thinning (if necessary)	DILUENTE MONOMERICO
Application temperature	+10°C ÷ +25°C
Application	Roller machine
Coverage	15/80 g/m ²
Hardening	1/3 mercury lamps 360
Sanding	Good
Dry residue	99%
Storage stability	6 months ⁽¹⁾
Packaging	25 Kg
Tool cleaning	DILUENTE ACETONE

1 in original sealed containers at temperatures between +10°C and +25°C

How to use

Shake well before use.

FONDO UV R37 - G10 is a suitable sanding filler for application by reverse roller coating machines; crosslinked by high-pressure UV lamps. FONDO UV R37 - G10 is generally applied over a primer such as PRYMER UV R120 or PRYMER UW R200. After FONDO UV R37 - G10 has hardened via 2/3 high power lamps, it can be sanded down using 320/400 paper grit.

Label elements

· For more information about the safe use of the product it is recommended to consult the latest version of the Safety Data Sheet.