

FONDO UV R372

UV satin base based on special acrylic resins



Description

FONDO UV R372 is a single-component satin primer used as a filler primer for varnishing wooden floors, furniture, doors, panels, etc. FONDO UV R372 has a high filling power, excellent distension, good sanding and excellent adhesion.

Characteristics

Preparation	photoactivated
Thinning (if necessary)	DILUENTE MONOMERICO
Application temperature	+10°C ÷ +25°C
Application	reverse / single head roller coater
Coverage	15-80 g/m ²
Hardening	1/3 mercury lamps
Sanding	excellent
Dry residue	99%
Viscosity	2000 cP
Storage stability	1 year ⁽¹⁾
Packaging	25 KG
Machine cleaning	DILUENTE ACETONE

1 in original sealed containers at temperatures between +10°C and +25°C

How to use

Mix well before use.

FONDO UV R372 is a sandable satin primer suitable for roller application, reverse and cross-linked coating type by means of 1/3 mercury UV lamps. FONDO UV R372 is generally applied over adhesion fillers type FONDO UV R372 (see its data sheet). FONDO UV R372 is over-varnishable, after sanding, with FINITURA UV R77 (see the relevant data sheet).

Mezclar bien antes de usar.

FONDO UV R372 es una imprimación satinada lijable adecuada para la aplicación de rodillos, tipo de revestimiento inverso y reticulado mediante lámparas UV de mercurio de 1/3. FONDO UV R372 se aplica generalmente sobre rellenos de adhesión tipo FONDO UV R372 (ver ficha técnica). FONDO UV R372 es sobrebarnizable, después del lijado, con FINITURA UV R77 (ver la ficha de datos correspondiente).

Label elements

For more information about the safe use of the product it is recommended to consult the latest version of the Safety Data Sheet.

These information are given from the best of our knowledge and technical experience. They are of general character and not binding in any way our company. Every single case should be put to a practical test by the user who assumes the full responsibility of the final result of his work.