

Technical Datasheet

Item Code: LGRC000X | Rev.: 29-07-2025 | Ver: 3.3

FONDO UV R378

UV primer for high abrasion resistance cycles



Description

FONDO UV R378 is a single-component primer used exclusively for varnishing wooden floors that require high abrasion resistance.

Characteristics

Mixture ratio	SINGLE-COMPONENT
Application temperature	+10°C ÷ +25°C
Application	roller coater / reverse
Thinning (if necessary)	DILUENTE MONOMERICO
Coverage	30-50 g/m ²
Dust dry	30' ⁽¹⁾
Sanding	DO NOT SAND
Dry residue	99%
Viscosity	>100" F6
Storage stability	6 months ⁽²⁾
Packaging	10 Kg
Tool cleaning	DILUENTE ACETONE

1 at 20°C and 65% R.H.

2 in original sealed containers at temperatures between +10°C and +25°C

How to use

Shake well before use.

FONDO UV R378 is a single-component primer suitable for application by roller coater / reverse and can be cured using 1 mercury UV lamp. FONDO UV R378 is used exclusively to achieve high abrasion resistance cycles. It is applied, in quantities not less than 30 g/m², over adhesion fillers such as PRYMER UV R120 (see relevant data sheet) and must be overcoated with a sandable primer such as FONDO UV R37 G10 (see relevant data sheet).

Label elements



· For more information about the safe use of the product it is recommended to consult the latest version of the Safety Data Sheet.

These information are given from the best of our knowledge and technical experience. They are of general character and not binding in any way our company. Every single case should be put to a practical test by the user who assumes the full responsibility of the final result of his work.