

Technical Datasheet

Item Code: LBIO050X | Rev.: 14-09-2026 | Ver: 3.9

LIOS B-OIL Colorato

Pigmented oil for wooden floors



Description

LIOS B-OIL Colorato is a colored oil treatment for wooden floors with easy application, very durable and soft effect on the surface. LIOS B-OIL Colorato is available in 18 different colors, miscible together to make a wide range of new colors.

Characteristics

Application	buffing machine, rubber trowel, floor polisher, sponge, cloths
Application temperature	+10°C ÷ +25°C
Thinning (if necessary)	LIOS SOLV
Surface dry time	24/48 h ⁽¹⁾
Total drying time	15-30 days ⁽¹⁾
Coverage	30-40 m²/L (depending of the sanding)
Storage stability	1 year ⁽²⁾
Packaging	1 L
Tool cleaning	DILUENTE DNE
1	at 20°C and 65% R.H.
2	in original sealed containers at temperatures between +10°C and +25°C

Available Versions

Range of colors :

* Chestnut	* Larch	* Dove-grey
* Vanilla	* Havana	* Cherry
* Dark oak	* Dark walnut	* Grey
* Smoky grey	* Classic walnut	* White
* Super White	* Black	* Wenge
* Teak	* Titanium Grey	* Stone
* on request		

How to use

Shake the product using a stick to have a homogeneous mixture.

LIOS B-OIL Colorato has to be applied to wooden floors that have been filled and sanded with 120 paper grit, than use High Pro felt disc to make the surface absorbs the product evenly. Alternatively, finish the floor with 150 paper grit. Apply LIOS B-OIL Colorato on the floor, working the product in order to help its penetration into the wood grain.

After 15-20 minuts buff the surface using a buffing machine with a white pad and a cloth to remove the excess of oil and have an uniform and smooth effect.

For small dimension rooms use a cloth instead a buffing machine.

After 24 hours, apply LIOS BALM FISSATIVO, OIL WOOD TRAFFIK, LIOS Natural Look Wax, OIL BEE (see technical data sheets).

After 72 hours it is possible to apply STAR 2K, TRAFFIK 2K, WOOD 2K or DUROLACK MC 50 (see technical data sheets).

Notes

In order to prevent future yellowing of the product, we strongly recommend to follow this cycle LIOS B-OIL Bianco / LIOS B-OIL Super Bianco and after 3 days apply one coat of CHIM TABU FD (see technical data sheet).

If the surface to be treated is wide, we suggest to pour all the cans of product into a big one and than proceed with the application.

An un-even sanding of the wooden floor causes not homogeneous absorption of the product.

Shipping notes.

The WHITE, SUPER WHITE and GREY versions are not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.

Warnings

Cloths, rollers, pads used for the application (even sanding dust), must be soaked in water immediately after use in order to avoid the risk of self-ignition.

Label elements

	For more information about the safe use of the product it is recommended to consult the latest version of the Safety Data Sheet.
--	--

Web link

Be sure to have the latest version of this technical data sheet downloadable also from the following link:



http://www.chimiver.com/tds/EN_LIOS_B-OIL_Colorato.pdf

These information are given from the best of our knowledge and technical experience. They are of general character and not binding in any way our company. Every single case should be put to a practical test by the user who assumes the full responsibility of the final result of his work.