

## Technical Datasheet

Item Code: LBAH000X | Rev.: 18-09-2023 | Ver: 3.4

# LIOS BALM Fissativo HV

*Natural protective agent for oil-finished floors by industrial application*



### Description

LIOS BALM Fissativo HV makes natural oil treated floors more durable and water-repellent.

### Characteristics

Application	spray, roller machine
Application temperature	+10°C ÷ +25°C
Viscosity	70" Ford 2
Thinning (if necessary)	diluyente LIOS SOLV
Surface dry time	12-24 h <sup>(1)</sup>
Total drying time	15 days <sup>(1)</sup>
Coverage	20-30 gr/m <sup>2</sup> (depending on the porosity of the wood)
Storage stability	1 year <sup>(2)</sup>
Packaging	25 lt
Tool cleaning	DILUENTE DNE

1 at 20°C and 65% R.H.

2 in original sealed containers at temperatures between +10°C and +30°C

### How to use

Shake well before use.

When using specific industrial plants for board staining, application of LIOS BALM Fissativo HV is mainly made with roller machines.

LIOS BALM Fissativo HV can normally be applied by spray, but needs immediate brushing to make the surface more uniform.

### Warnings

*Cloths, sponges, pads used for the application (even sanding dust), must be soaked immediately after use in order to avoid the risk of self-ignition.*

### Label elements



· For more information about the safe use of the product it is recommended to consult the latest version of the Safety Data Sheet.

These information are given from the best of our knowledge and technical experience. They are of general character and not binding in any way our company. Every single case should be put to a practical test by the user who assumes the full responsibility of the final result of his work.