

Technical Datasheet

Item Code: VNAT000X | Rev.: 11-09-2026 | Ver: 3.6

LIOS NATURAL LOOK WAX

Waxes blend for the treatment of wooden floors



Description

LIOS NATURAL LOOK WAX is a wax blend recommended for the treatment of wooden floors, cotto floors and furnitures. The treated materials have an excellent superficial hardness and glossiness. The waxed floors whitening, due to water absorption, is reduced by using waxes.

Characteristics

Mixture ratio	single-component
Application temperature	+10°C ÷ +25°C
Application	rubber trowel, cloth, buffing machine
Surface dry time	12-24 h ⁽¹⁾
Total drying time	2 weeks ⁽¹⁾
Thinning (if necessary)	LIOS SOLV
Coverage	1 L / 25-30 m ²
Storage stability	1 year ⁽²⁾
Packaging	1 L - 5 L
Tool cleaning	LIOS SOLV (with fresh product)
1	at 20°C and 65% R.H.
2	in original sealed containers at temperatures between +10°C and +25°C

How to use

Shake well before use.

LIOS NATURAL LOOK WAX has to be applied to wooden floors that have been filled and sanded with 100/120 paper grit, than use High Pro felt disc to make the surface absorbs the product evenly. Alternatively, finish the floor with 150 paper grit. Apply LIOS NATURAL LOOK WAX by cloth or buffing machine on the floor, working the product in order to help its penetration into the wood grain, without leaving any excess of product.

After 15-20 minuts buff the surfaces using a buffing machine with a white pad and a cloth to remove the excess of oil and have an uniform and smooth effect.

The best result is obtained after the application of 2/3 coats of LIOS NATURAL LOOK WAX.

Application on cotto tiles:

Apply LIOS NATURAL LOOK WAX by cloth or buffing machine, working the product in order to help its penetration into the wood grain, without leaving any excess of product. If the desired result has not been obtained, it is suggested to apply another coat of LIOS NATURAL LOOK WAX. In case of strongly absorbent floors, it is advisable to apply WAX CARE (see relative technical data sheet).

Maintenance

Remove by cloth, using LIOS SOLV (see relative technical data sheet) if present, any sole black marks. Apply by cloth LIOS NATURAL LOOK WAX diluted with LIOS SOLV in ratio 1:1, after the complete drying it is possible to buff the surface.

The ordinary and extraordinary maintenance have to be done with VELUREX CLEANER STAR (see relative technical data sheet).

Warnings

Keep out of children's reach. Do not drink nor inhale. Avoid contact with eyes.

Label elements

For more information about the safe use of the product it is recommended to consult the latest version of the Safety Data Sheet.

These information are given from the best of our knowledge and technical experience. They are of general character and not binding in any way our company. Every single case should be put to a pratical test by the user who assumes the full responsibility of the final result of his work.