

LIOS SUNDECK WOOD OIL

Impregnator for outdoor wooden floors



Description

LIOS SUNDECK WOOD OIL is an outdoor wood impregnator particularly recommended for the treatment of outdoor wooden floors (swimming pool edges, verandas, walkways), window and door frames, fences and canopies made of wood. It contains natural and synthetic oils, with the addition of UV ray absorbers and special anti-ageing ingredients against the wood decay. It doesn't crack. Also available in LIGHT version, which doesn't alterate the natural colour of wood, particularly indicated for the treatment of south-american species (i.e. IPÉ Lapacho, Tobacco etc.) and other similar types of outdoor woods painted in autoclave (usually green colour). Doesn't degrade rubbers and expansion joints. It is recommended anyway to make some tests before application.

Characteristics

Mixture ratio	single-component
Application temperature	+10°C ÷ +25°C
Application	Brush, Rag
Thinning (if necessary)	LIOS SOLV
Coverage	1 L/13 m ² ca
Dust dry	6 h ⁽¹⁾
Fingerprint dry	24 h ⁽¹⁾
Storage stability	1 year ⁽²⁾
Packaging	1 L - 5 L
Tool cleaning	LIOS SOLV

1 at 20°C and 65% R.H.

2 in original sealed containers at temperatures between +10°C and +25°C

Available Versions

STANDARD: slightly colored in order to give a warm tone to the decking.

LIGHT: transparent to keep the natural wood color.

How to use

Shake well before use. Before applying LIOS SUNDECK WOOD OIL, prepare the wood, preferably with 100 sandpaper. Apply the first coat of LIOS SUNDECK WOOD OIL by brush or rag, avoiding excesses. A few minutes after application, it's possible to use a clean brush to remove excesses of product. If necessary, apply a second coat after 24/48 hours, without sanding.

Warnings

Rags, sponges, brush used for the application (even sanding dust), must be soaked immediately after use in order to avoid the risk of self-ignition.

Warnings

Once the tin has been opened, prolonged storage of the product may result in the formation of a surface film on it. This skin does not compromise the characteristics of the product, which can be used after the removal of the skin formed and diluting the product with LIOS SOLV or mineral spirits.

Cleaning and general maintenance

To wash and clean outdoor floors, use LIOS SUNDECK SOAP (nourishing detergent) following the instructions for use. It efficiently removes dirt, traces of chlorine and salt etc.

As maintenance product we recommend LIOS SUNDECK SOAP every 15 days (see technical data sheet).

Label elements

For more information about the safe use of the product it is recommended to consult the latest version of the Safety Data Sheet.

Web link

Be sure to have the latest version of this technical data sheet downloadable also from the following link:



http://www.chimiver.com/tds/EN_LIOS_SUNDECK_WOOD_OIL.pdf