

PARKETKIT

Colored acrylic filler parkettkit



Description

PARKETKIT is a acrylic filler to seal baseboards, joints, between differing flooring elements, etc. May be over-coatable easily after the complete hardening.

Characteristics

Mixture ratio	single-component
Application temperature	+10°C ÷ +25°C
Application	silicone gun
Colour	oak, walnut, doussiè, iroko, beech-cherry, maple, white, wenge', gray, beige
Joint coverage for leakage 5x5	aprox. 12 linear meters
Joint coverage for leakage 10x10	aprox. 3 linear meters
mm	
Specific weight	white 1,6 kg/L coloured 1,65 kg/L
Maximum open time	15-20' ⁽¹⁾
Complete hardening	18-24 h ⁽¹⁾
Storage stability	18 months ⁽²⁾
Packaging	310 ml
Tool cleaning	water (with fresh adhesive)
1	at 20°C and 65% R.H. for leakage 3/4 mm
2	in original sealed containers at temperatures between +10°C and +25°C

How to use

PARKETKIT may only used on perfectly clean, degreased and dust-free surfaces. After applying, smooth out the joint with a trowel or wet sponge. Repeat the application in case of excess shrinking. After 24 h from the application may be sanded.

Warnings

For temperatures above 30°C, provide a consumption for a 20% higher. Maximum material allowance is 15 x 15 mm. Low temperatures, high humidity and a considerable leakage can slow down the hardening of the adhesive.

Label elements

For more information about the safe use of the product it is recommended to consult the latest version of the Safety Data Sheet.

Web link

Be sure to have the latest version of this technical data sheet downloadable also from the following link:



http://www.chimiver.com/tds/EN_PARKETKIT.pdf