

# PRYMER UW R200

**UV Primer based on special resins**



## Description

Single-component photoactivated product based on special resins used as a primer coat for varnishing parquet, furniture, doors and panels. Equipped with excellent mechanical performance, toughness and transparency; it is used as an adhesion coat on woods that are particularly difficult to treat.

## Characteristics

Preparation	photoactivated
Thinning (if necessary)	water
Application temperature	+10°C ÷ +25°C
Application	roller machine
Coverage	10/15 g/m <sup>2</sup>
Hardening	1 mercury lamps 360
Pot-Life	n.a.
Sanding	n.a.
Overcoating without sanding	n.a.
Wood oxidation	good
Dry residue	40%
Viscosity	30" - 40" Ford Cup 6
Specific weight	1,0 Kg/L
Physical characteristics	excellent
Storage stability	1 year <sup>(1)</sup>
Packaging	25 KG
Machine cleaning	water - DILUENTE ACETONE

1 in original sealed containers at temperatures between +10°C and +25°C

## How to use

Shake well before use.

PRYMER UW R200 is an adhesion primer suitable for application by roller machines like spreader and crosslinkable by high pressure UV lamps. PRYMER UW R200 is used as a bonding coat on woods particularly difficult to treat and, after semi-drying by 1 at lamp high pressure, overpainted with UV filler/sanded.

## Label elements



For more information about the safe use of the product it is recommended to consult the latest version of the Safety Data Sheet.