

PRYMER UW R400

Natural effect UV primer

Description

Photoactivated single-component product based on special resins used as a primer to coat parquet, furniture, doors and panels. Equipped with excellent mechanical performance, toughness and transparency; it is used to maintain a natural effect in UV roller cycles.

Characteristics

Preparation	Photoactivated
Thinning (if necessary)	Water
Application temperature	+10°C ÷ +25°C
Application	Roller machine
Coverage	10 - 15 g/m ²
Hardening	1 mercury lamp
Viscosity	30" - 40" DIN 6
Specific weight	1 Kg/L
Chemical and physical characteristics	excellent
Storage stability	1 year ⁽¹⁾
Packaging	25 KG
Machine cleaning	Water - DILUENTE ACETONE

1 in original sealed containers at temperatures between +10°C and +25°C

How to use

Shake well before use.

PRYMER UW R400 is an adhesion primer that is suitable for application by roller coating machines and cross-linked with high-pressure UV lamps. PRYMER UW R400 is used to maintain a natural effect in UV roller cycles and, after partial drying by means of 1 high pressure lamp, overcoated with a UV filler/sandable primer.

Label elements

	<p>For more information about the safe use of the product it is recommended to consult the latest version of the Safety Data Sheet.</p>
--	---

These information are given from the best of our knowledge and technical experience. They are of general character and not binding in any way our company. Every single case should be put to a practical test by the user who assumes the full responsibility of the final result of his work.