

RAINCOAT FLOOR

Water-based impregnator for outdoor wood



Description

RAINCOAT FLOOR is a water-based impregnating oil for wood. It's particularly suitable for the treatment of wooden floors located outside as swimming pool edges, verandas, walkways, window and door frames, fences and canopies made of wood. RAINCOAT FLOOR is composed of emulsified oils and water-based resins, reactive elements that bind to the wood lignin, strengthening it and delaying the wood decay (graying) significantly.

Characteristics

Mixture ratio	single-component
Application temperature	+10°C ÷ +25°C
Application	cloth, brush, immersion, wax applicator
Thinning (if necessary)	water
Coverage	1 L/10 m ²
Dust dry	2 h ⁽¹⁾
Fingerprint dry	4 h ⁽¹⁾
Sanding	do not sand
Storage stability	1 year ⁽²⁾
Packaging	1 L
Tool cleaning	DILUENTE DNH 40 (with fresh product)

1 at 20°C and 65% R.H.

2 in original sealed containers at temperatures between +10°C and +25°C

Available Versions

RAINCOAT FLOOR :

STANDARD: slightly colored in order to give a warm tone to the decking.

LIGHT: transparent to keep the natural wood color.

COLORATO: available on request.

How to use

Before applying RAINCOAT FLOOR shake well and prepare the wood, preferably with 120 sandpaper. Apply a coat of RAINCOAT FLOOR with a brush along the wood grain, trying to avoid application interruptions. After 2-4 hours apply a second coat without sanding in the same way. In order to avoid any differences in color or any overlapping, it is suggested to spread well and uniformly the product on the surface without leaving any excess. The application of RAINCOAT FLOOR is suggested when the temperature of the floor is not high and anyway without direct sunlight. If the application has to be done under direct sunlight, moisten the floor before the application of RAINCOAT FLOOR. Do not apply with temperature over +30°C.

Cleaning and maintenance

To wash and clean outdoor floors, use LIOS Sundeck Soap (nourishing detergent) following the instructions for use. It efficiently removes dirt, traces of chlorine and salt etc.

Notes:

For the application of RAINCOAT FLOOR white, grey or light colors is recommended to make preliminary tests on the wood species to be treated (especially on garapà, ipè lapacho, ecc.) in order to prevent undesired "bleeding effects".

As maintenance product we recommend LIOS Sundeck Soap every 15 days (see technical data sheet).

Label elements

For more information about the safe use of the product it is recommended to consult the latest version of the Safety Data Sheet.