

Technical Datasheet

Item Code: MLTSCAC0000 | Rev.: 29-06-2022 | Ver: 3.1

SERIE CAC

Water-based pigment concentrates for dyes



¤Description

Dispersion of high concentration pigments in water with high light stability and excellent coverage. No bleeding effect, good levelling power, excellent resistance to overpainting, excellent resistance to overpainting with polyurethane, acrylic and photocross-linked products. Mainly used for the preparation of semi-covering dyes for the painting of woody essences for indoor use.

¤Characteristics		
Appearance	liquid	
Application	brush, rag, spray, roller	
Thinning (if necessary)	water	
Application temperature	+10°C ÷ +25°C	
Storage stability	1 year ⁽¹⁾	
Packaging	1L-5L	

¹ in original sealed containers at temperatures between +10°C and +25°C

***Available Versions**

0010 Giallo medio	0020 Rosso ossido	0021 Magenta
0080 Nero	0090 Bianco	- OOLI Magemea

¤How to use

CAC are not ready to use, but need dilution which can vary according to the desired intensity and kind of application. Diluted and in combination with special vehicles can be applied by spraying or with roller coaters. They can be mixed with concentrates of the CUC series in any concentration so to obtain variations of coverage and brilliance. CAC are suitable for coloring indoor water-based finishes.

¤Label elements



· For more information about the safe use of the product it is recommended to consult the latest version of the Safety Data Sheet.

These information are given from the best of our knowledge and technical experience. They are of general character and not binding in any way our company. Every single case should be put to a pratical test by the user who assumes the full responsability of the final result of his work.