

# Technical Datasheet

Item Code: MLTSCSC0000 | Rev.: 15-09-2023 | Ver: 3.3

# **SERIE CSC**

# Solvent-based pigment concentrates for dyes



## **¤**Description

Dispersion of high concentration pigments in suitable organic solvents characterized by high light stability and excellent coverage. No bleeding effect, good shine, good levelling power, excellent resistance to overpainting with polyurethane, acrylic and photocross-linked products. Mainly used for the preparation of semi-covering dyes for the painting of woody essences for indoor use.

<b>¤</b> Characteristics		
Appearance	liquid	
Application	brush, rag, spray, roller	
Thinning (if necessary)	DLC-0044; DLC-0022; DMC-0070;	
	DNS-0018; DMC-0029	
Application temperature	+10°C ÷ +25°C	
Storage stability	1 year <sup>(1)</sup>	
Packaging	1 L - 5 L	
	••••••	

in original sealed containers at temperatures between +10°C and +25°C

#### **\*Available Versions**

0010 Giallo ossido	0011 Giallo cromo	0020 Rosso ossido
0050 Verde	0060 Bruno	0080 Nero
0090 Bianco	0061 Bruno scuro	

#### #How to use

CSCs are not ready-to-use dyes, but require a dilution that can vary depending on the desired intensity and the type of application. Diluted in suitable organic solvents and in combination with special vehicles, they can be applied manually, by spray or with roller painters. They can be mixed with CUC series concentrates in all ratios to obtain variations in coverage and gloss.

### **¤Label elements**



· For more information about the safe use of the product it is recommended to consult the latest version of the Safety Data Sheet.

These information are given from the best of our knowledge and technical experience. They are of general character and not binding in any way our company. Every single case should be put to a pratical test by the user who assumes the full responsability of the final result of his work.