

Technical Datasheet

Item Code: SLOW000X | Rev.: 14-01-2026 | Ver: 3.4

SLOWER-

Retarding additive for polyurethane adhesives



■ Description

SLOWER- is an retarding additive for two-component polyurethane adhesives, specifically formulated for ADESIVER GREEN TURF/ADESIVER 327 PU /ADESIVER RE 702. It is used to slow down the setting time of the adhesive and installation of the flooring.

■ Characteristics

Appearance	liquid
Packaging	240 g
Maximum mixing ratio	240 g ⁽¹⁾

1 for each 11,8 Kg container of two-component polyurethane adhesive

■ How to use

Add SLOWER- to component A and mix with an electric drill at low rpm until completely homogeneous. Add component B and proceed as usual.

Notes:

Use a maximum of 240 g for each 11,8 Kg can.

POT LIFE of ADESIVER GREEN TURF at different temperatures

	10°C	20°C	35°C
ADESIVER GREEN TURF	80 min	65 min	45 min
+ 2% SLOWER-	/	/	65 min

■ Label elements

 · For more information about the safe use of the product it is recommended to consult the latest version of the Safety Data Sheet.

■ Web link

Be sure to have the latest version of this technical data sheet downloadable also from the following link:



http://www.chimiver.com/tds/EN_SLOWER-.pdf

These information are given from the best of our knowledge and technical experience. They are of general character and not binding in any way our company. Every single case should be put to a practical test by the user who assumes the full responsibility of the final result of his work.