

# SPAGHETTO DECK

Joint rope for the pre-filling of caulking deck



## Description

SPAGHETTO DECK is a polyethylene sponge rope with round section for the pre-filling of caulking deck that has to be filled with ELASTOXYL.

## Characteristics

Colour	grey
Specific weight	35 Kg/m <sup>3</sup>
Solvent resistance	good
Water resistance	good
Dimensional stability	excellent
Temperature resistance	from -40°C to +75°C
Rope diameter	8 mm - 10 mm - 15 mm
Packaging	1500 mt - 750 mt - 550 mt

## How to use

Clean and vacuum very well the joint surface than insert manually SPAGHETTO DECK on the bottom of the joint. It is advisable to use a rope with a higher diameter up to 1,5 times of the joint width. After the right positioning of SPAGHETTO DECK proceed with the application of ELASTOXYL (see technical data sheet).

## Label elements



· For more information about the safe use of the product it is recommended to consult the latest version of the Safety Data Sheet.

## Web link

Be sure to have the latest version of this technical data sheet downloadable also from the following link:



[http://www.chimiver.com/tds/EN\\_SPAGHETTO\\_DECK.pdf](http://www.chimiver.com/tds/EN_SPAGHETTO_DECK.pdf)

These information are given from the best of our knowledge and technical experience. They are of general character and not binding in any way our company. Every single case should be put to a practical test by the user who assumes the full responsibility of the final result of his work.