

STUCCO W

Water-based putty for wooden floors



Description

STUCCO W is a single-component ready to use product ideal for putting small defects on the surface of the wooden floors before proceeding to the final lacquering.

Characteristics

Application temperature	+10°C ÷ +25°C
Colour	different colours available
Application	smoothed trowel
Thinning (if necessary)	water
Storage stability	1 year ⁽¹⁾
Packaging	1 kg
Tool cleaning	water

1 in original sealed containers at temperatures between +10°C and +25°C

How to use

Shake well before use.

Apply STUCCO W directly onto affected parts that have already been cleaned and vacuumed thoroughly. Wait about 1 h, until the surface is completely dry, then proceed with the normal sanding application. For very deep defects, repeat the operation. Remove excess parts to avoid "coloration" defect in the next lacquering application.

STUCCO W can be over-varnished with ECORAPID, ECOSTARTER, ECOCROM, ECOPRIME HS 120, FONDO WR 306 or OIL WOOD TRAFFIK (see technical data sheets).

NOTES:

the over-coating with ECOSTAR 2K (see technical data sheet) is not suggested, polishing of the joints can be faced.

Label elements



For more information about the safe use of the product it is recommended to consult the latest version of the Safety Data Sheet.

Web link

Be sure to have the latest version of this technical data sheet downloadable also from the following link:



http://www.chimiver.com/tds/EN_STUCCO_W.pdf

These information are given from the best of our knowledge and technical experience. They are of general character and not binding in any way our company. Every single case should be put to a practical test by the user who assumes the full responsibility of the final result of his work.