

Technical Datasheet

Item Code: VPOL000X | Rev.: 29-06-2022 | Ver: 3.2

VELUREX Polish WT

Water-based maintenance wax for wooden floors



Description

VELUREX POLISH WT is a water-based emulsion of waxes. It is developed for the maintenance of lacquered wooden floors, rubber floors, vinyl floors, linoleum, marble, resins, etc. (not good for maintenance of oiled wooden floors or not-absorbent building materials). The product gives to the floor very good antistatic characteristics. It nourishes and restores at the same time, leaving a pleasant fragrance in the ambient.

¤Characteristics

Application temperature	+10°C ÷ +25°C
Application	cloth
Thinning	water
Coverage	1 L / 70 m²
Storage stability	1 year ⁽¹⁾
Packaging	1 L - 5 L - 10 L - 25 L
Tool cleaning	Water

in original sealed containers at temperatures between +10°C and +25°C

#How to use

1 L packaging: dilute 3 caps into 1L of water. Apply evenly by soft cotton cloth and wait until completely dry (20-30 mins). Polish the surface with soft cloth or proper equipment.

Recommended use once or twice a month.

***Warnings**

Keep out of children's reach. If medical advice needed, have product container or label at hand.

¤Label elements



· For more information about the safe use of the product it is recommended to consult the latest version of the Safety Data Sheet.

#Web link

Be sure to have the latest version of this technical data sheet downloadable also from the following link:



http://www.chimiver.com/tds/EN_VELUREX_Polish_WT.pdf

These information are given from the best of our knowledge and technical experience. They are of general character and not binding in any way our company. Every single case should be put to a pratical test by the user who assumes the full responsability of the final result of his work.